

ID Bridge CT30 USB smartcard reader



The IDBridge CT30 (formerly the GemPC Twin/TR from Gemalto) is a USB desktop reader from Thales, which integrates high quality and functionality with a contemporary design. This reader is fully PC/SC and EMV Level 1 compliant and supports all ISO 7816 microprocessor-based smartcards as well as many popular memory cards.

Simple plug-and-play operation on Windows.

The IDBridge CT30 is compact and boasts performance to match many other leading brand readers. This unique transparent reader even allows you to see the card when inserted. This version has a fixed USB cable.

There is a software and hardware proof of concept kit for PKI-based logon, which includes this card reader.

Thales part number 962-000009-004

*****Call +44 (0)1483 685250 for our best price reseller deals on bulk orders or email sales@dotdistribution.com*****

This unique transparent USB contact reader is highly compact and boasts high performance to match.

To buy, visit:

<https://www.smartcardfocus.com/shop/ilp/id~463/p/index.shtml>

This Product Briefing has been produced by Dot Origin Ltd, the smart card experts behind SmartcardFocus.com. If you have a query email sales@smartcardfocus.com or call us on +44 (0)1428 685250.

Technical Specifications

Product:

Credential type(s): Contact

Form factor: Portable

Connector: USB CCID (Standard 2.0 Type A connector)

OS support: Up to Windows 11 (including 7, 8.1), Linux, MacOS; drivers available from [Thales Customer Support Portal](#)

Contact Smartcard Interface:

Contact interface standard: ISO 7816

Contact card types: Processor cards (T=0 and T=1)

Card Voltage 5V, 3V & 1.8V

Data transmission protocol: T=0 / T=1

Card contacts: Sliding

Contact read/write speed: 2kbps - 826kbps

Clock frequency: 4.8MHz

Card insertion cycles: Min 100 000

Host Interface:

Host interface standards: PC/SC

Host data transmission speed (wired): 12 Mbps (USB full speed)

Other Features:

Card detection: Card insertion/extraction detection, Short circuit protection

Status indicator: Green LED with dual state (waiting and operation)

An additional desktop stand is available as an accessory.

Certifications:

Manufacturer's warranty: 2 year

Type approvals: CE, FCC part 15, RoHS 2, REACH, WEEE, IEC 60950, c-Tick

Application approvals: EMV Level 1 (Contact), c-Tick (Australia), VCCI (Japan), BSMI (Taiwan)

Country of origin: China

Physical:

Dimensions: 74 x 63 x 13mm (2.9 x 2.5 x 0.5in)

Weight (±5%): 55g (1.9oz)

Cable length supplied: 1.5m (59.1in)

Power:

Supply voltage: 5V DC

Operating current: Less than 200µA (in suspend mode)

Battery power option: No

Environment:

Operating temperature: 0 to 55degC (32 to 131degF)

Storage temperature: 0 to 70degC (32 to 158degF)

Operating humidity: 10-95% RH (non-condensing)

Manufacturer's part number: 962-000009

Country of origin: China

HSF code: 8471900000

Manufacturer: Thales

Connection Method: USB