

MIFARE Ultralight Tag



The MIFARE Ultralight chip from NXP in miniature self-adhesive tag format. Operates at 13.56 MHz wireless frequency, according to the ISO 14443A standard. Contains 48 bytes of usable read/write memory, with no security protection.

Less than 1mm thick these tags are ideal for use with NFC applications.

This tag is NFC forum type 2 compliant.

Supplied as white 25mm x 15mm self-adhesive tags.

Limited stock remaining

Less than 1mm thick, 64 byte contactless tag ideal for NFC applications. Operates at 13.56 MHz. 25mm x 15mm.

To buy, visit:

<https://www.smartcardfocus.com/shop/ilp/id~277/mifare-ultralight-tag/p/index.shtml>

This Product Briefing has been produced by [Dot Origin Ltd](#), the smart card experts behind [SmartcardFocus.com](#). If you have a query email sales@smartcardfocus.com or call us on +44 (0)1428 685250.

MIFARE Ultralight

MIFARE, RF Interface (ISO/IEC 14443 A)

Operating distance: Up to 100mm

Operating frequency: 13.56 MHz

Data transfer: 106 kbit/s

Data integrity: 16 Bit CRC, parity, bit coding, bit counting

Typical ticketing transaction: <35 ms (including backup management)

Fast counter transaction: <10 ms (including backup management)

EEPROM

512 bit, organised in 16 pages with 4 byte each

Field programmable read-only locking function per page

32 bit user definable One Time Programmable (OTP) area

384 bit user r/w area (12 pages)

Data retention of 5 years

Write endurance 100 000 cycles

Security

Anti-cloning support by unique 7 Byte serial number for each device

32 Bit user programmable OTP area

Field programmable read-only locking function per page

Further images of the **MIFARE Ultralight All Surface Tag - 35 mm** and **MIFARE Ultralight All Surface Tag - 50 mm Engraved** are shown below.



Manufacturer: NXP