

### Mobile pass NFC reader

A contactless reader that interacts with mobile phones as well as popular RFID cards and tags. The VTAP100 from Dot Origin retrieves NFC wallet passes from iPhone and Android devices, using a simple tap, then decrypts and transfers that pass data to other systems.

Pass users only need the Apple or Google Wallet app. The VTAP100 is fully certified by both Apple and Google for VAS and Smart Tap protocols.



### Quick deployment

The VTAP100 has been designed specifically for mobile pass applications. It includes features such as automatic pass selection, even when the screen is off (on iOS). It can also read popular contactless NFC and RFID cards and tags, to support mixed use applications and easy migration away from plastic. It can emulate a barcode/QR code scanner and can be configured to selectively extract and send on pass data in formats already in use. The VTAP100 can be easily retrofitted to existing systems, or quickly integrated into new platforms, for a smooth transition to an Apple and Google digital wallet card experience.

### Easy management

Configuration of VTAP100 operating parameters is done over any host interface, USB or serial. The file-based approach is platform independent and requires no drivers or dedicated software. For serial file transfers, the ZModem protocol is used with active (send on tap) and passive (command/response) interface options. Flexible and intuitive settings can be edited manually or by software, and real-time commands can be sent. They include support for multiple pass profiles and private keys, plus tailored user feedback over RGB LEDs and a buzzer.

### Strong security

The VTAP100 has been designed with security in mind and includes a dedicated hardware key storage chip to protect the merchant private keys needed to decrypt pass data. So it is not possible to extract the keys once loaded, although they can be updated easily, in standard file formats. The device firmware can also be updated as an encrypted file.

Password protection of all configuration data is available, with reset to factory defaults if needed, clearing all sensitive data. MIFARE secure sector reading is also implemented to support migration from legacy systems.

### Flexible form factor

The VTAP100-USB is in a compact desktop or wall-mounting case. It has a recess for a custom-printed front label, to suit application and branding requirements.

Other models offer different electronic interface options, including Wiegand, RS-232 and RS-485 for access control. A pre-certified OEM reader-board is also available for embedded applications.

Learn more on the VTAP website at <https://vtapnfc.com>.

# VTAP100-USB-CC SPECIFICATION

For information on pricing and availability email [vtap-sales@dotorigin.com](mailto:vtap-sales@dotorigin.com)

Physical characteristics	
Dimensions	97mm x 49mm x 40mm (3.8in x 1.9in x 1.6in)
Front label	41mm x 57mm (1.61in x 2.24in) with 2mm (0.08in) radius corners
Power supply	5V DC (typ. 110mA, max 150mA)
Mounting options	2 x mounting holes in base plate, 1 x security screw fixing front part
Weight	44g (1.6oz)
Operating Temperature	-25 to +70°C (-13 to 158°F)
Operating Humidity	0 to 95% RH non-condensing
NFC interface	
Frequency/standards	13.56MHz, ISO 14443 and ISO 18092
Mobile pass compatibility	Apple Wallet NFC passes (VAS protocol – classed as a VAS-only device) Google Wallet NFC passes (Smart Tap protocol) Pass auto-selection, including full Apple ECP compliance for iOS wake-up; Selective field extraction & decryption of pass data; Mobile device type detection and inclusion; Multiple simultaneous pass IDs, enrolment URL and STUID capture, where supported on mobile OS
Card/tag compatibility	MIFARE Ultralight, Classic, DESFire, NFC Types 1..4 UID/CSN reading as standard on all card types Secure data reading on MIFARE Classic as standard, others on request NFC tag reading on Type 2 & 4 (Ultralight/NTAG and DESFire/HCE)
Read range	Typically 25mm (1in) depending on environment and phone/card/tag antenna
Pass IDs	Up to 6 x Apple merchant IDs and 6 x Google collector IDs
ECC key slots	6 total (shared between Apple & Google merchant IDs)
USB	
USB device types (can enable/disable as required)	USB Mass storage (for easy configuration, key loading & firmware updates) Human interface device (standard barcode reader/keyboard emulation) USB Virtual COM port (includes active, passive and file transfer modes)
Connector	Captive USB cable
Operating system support	Full support on Windows, Linux, OSX; support for keyboard emulation and virtual COM device types on Android; most other operating systems support keyboard emulation
Other features	
Operator feedback	Buzzer and RGB LEDs (configurable default colour + automatic card and pass read beep/flash)
Field configurable	Yes, using configuration files, and with password and hardware-based lock
Field upgradeable	Yes, using encrypted firmware file and secure bootloader, and factory reset feature
Hardware security	Cryptographic co-processor with secure hardware-based key storage
Encryption algorithms	ECDH, NIST P-256, ECDSA, HMAC SHA-256, AES-128 CTR, AES-256 GCM ANSI-X9.63-KDF & HKDF according to RFC5869 using HMAC-SHA256
Compliance/Certification	
Apple VAS, Google Smart Tap, UKCA, CE, FCC, NCC, RoHS	
24-month limited hardware warranty	

NOVEMBER 2022 PATENT PENDING  
©2020-2022 DOT ORIGIN LTD

